

The Enviroven™ Veneer collection delivers the warmth and texture of solid timber in a lightweight, durable and fully customisable form.

Available in a selection of colours, cuts, panel widths, and textures, including everything from natural wood grains to exciting contemporary looks, Enviroven™ Veneer is loved by designers for its consistency and versatility.

APPLICATION

Enviroven™ Veneers are the ideal choice for any interior application where conventional timber veneers could be used. Best of all, customising your design is easy with Enviroven™ Veneers. Enviroven™ Veneers unique versatility makes it ideal for small to large residential and commercial applications including complete commercial fit outs for the hospitality sector. Specific applications include:

- Wall and acoustic panelling
- Joinery
- Doors
- Furniture

TECHNICAL & DESIGN ADVANTAGES

Loved by designers for its consistency and versatility. As a reconstructed veneer, Enviroven™ Veneer offers consistency in woodgrain structure and tone across each panel, creating the ideal surface for large or small installations. The veneer panels are available in a broad selection of colours, cuts, panel widths and textures, including everything from natural wood grains to bold contemporary looks. Predictability in the look and texture of the veneer is assured over conventional veneers due to Enviroven™ Veneer's manufacturing process.

Enviroven™ Veneer gives you the freedom to create your look. Supplied unfinished with the grain running vertically along the length of the leaf, you decide on the final look you wish to achieve. Enviroven™ Veneer may also be laid on your substrate of choice and offers a matching selection of machine-veneered edging for a professional finish to your project.

The environmentally sustainable choice in timber veneers. Whether you choose an Enviroven™ Veneer sourced from European plantations or exotic locations in Africa, your product is guaranteed to meet our sustainable sourcing criteria, which includes:

- Strict forest management practices.
- Sourcing veneers that have been carefully peeled from controlled origin timbers and reconstructed to optimise consistency in colour and grain.
- A manufacturing process for the entire range that uses E1 certified urea formaldehyde glues and premium quality water based dyes.
- Strict FSC® requirements with selected Enviroven decors being FSC® chain of custody certified.



The mark of responsible forestry

WHAT FINISHING IS RECOMMENDED?

Some polyurethanes are more yellow than others and may also become more yellow with age. To minimise this, we suggest using 2-Pac Polyurethane with an added Non Yellowing Agent and UV Inhibitor.

For more information on the polishes available please refer to relevant suppliers of these products.

CLEANING & MAINTENANCE

How To Clean

Enviroven™ Veneer surfaces are easy to clean. Simply use a cloth dampened with warm water and detergent, or a solution of 1 part methylated spirits to 20 parts water. For more resistant stains we recommend using 100% methylated spirits or other light solvents. If in doubt about a particular cleaner or detergent, check with its manufacturer for suitability.

Avoid the following when cleaning:

- Acetone or trichloroethylene
- Abrasive cleaners, harsh detergents and powders
- Scouring pads, steel wool and sandpaper
- Ceramic cooktop cleaners
- Bathroom and tile cleaners
- Oven cleaners
- Chlorine bleach

These substances and materials could damage the finish of your Enviroven™ Veneer panels and make the surface susceptible to staining. Accidental spills or splatters of these harsh detergents and solutions should be wiped off immediately and the area cleaned thoroughly with a damp cloth.

For information regarding touch ups and repairs please visit newageveneers.com.au

TECHNICAL SPECIFICATIONS

Panel Size

2400mm x 1200mm, 2700mm x 1200mm, 3000mm x 1200mm

Panels come in 3 dimensions, each with variable thickness options. Refer to your local NAV representative for specifications and we will manufacture your panels to order.

Please note: Not every veneer colour is available in all sizes listed above. To see which veneers are available within each size group, please visit our Enviroven™ Veneers page on our website and select the Enviroven™ Veneer Checklist link.

COLOUR CONSISTENCY

Enviroven™ Veneer's colour consistency is obtained to an acceptable level with only subtle grain difference within block lots of up to 1,100 leaves of veneer.

In some veneers there can be colour variance of up to 10% from block to block as a result of batch dyeing. To minimise the chance of this occurring it is important that your specifier advise NAV in writing of their requirements or large projects.

GUARANTEE

NAV guarantees the intrinsic qualities of Enviroven™ Veneers. Discolouration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of NAV is limited to the replacement of any material shown to be defective. NAV reserves the right to discontinue any designs or products without notice at any time.