

Navurban is a contemporary take on decorative surfaces, offering a striking collection of environmentally preferable designs that feature the innovative surface technologies from Japan.

Navurban's unique finish delivers a 3D embossed surface texture with advanced performance characteristics. The embossing creates a tactile surface in a range of effects, including finely textured woodgrains; smooth and dry finishes; cross grain or rough-sawn qualities; and heavily textured woodgrains.

APPLICATION

Navurban is suitable for any interior application where conventional veneers could be used, with the added advantage of being a finished product. Navurban has strength, durability and aesthetic appeal that make it a versatile material ideally suited for, kitchens, bathrooms, commercial fit outs and furniture.

FABRICATION

Panel saws or table saws may be used to cut Navurban. Routers for trimming edges must have a smooth, clean base plate, so that the surface will not be scratched. Use carbide-tipped bits with ball bearing guide rolls. Keep all bits sharp. Drilling into Navurban may be done with standard wood bits or with router bits. For a final edge finishing use a flat smooth or fine file.

GRAIN DIRECTION

Navurban grain runs vertically along the length of the panel, with a select range also available with the grain running horizontal. Please refer to the Product Specification List for details.

MAINTENANCE

Navurban surfaces are easy to clean using a cloth dampened with warm water and detergent, or a solution of 1 part methylated spirits to 20 parts water. In case of more resistant stains we recommend to using 100% methylated spirits or other light solvents. If in doubt about a particular cleaner or detergent, check with its manufacturer for the suitability. We recommend you test on a small area or sample prior to applying to the surface.

Avoid the use of acetone or trichloroethylene for cleaning purposes. Use of abrasive cleaners, powders, scouring pads, steel wool, sandpaper etc. can damage the finish and make the surface susceptible to staining. Accidental spills or splatters from these harsh materials should be wiped off immediately, and the area cleaned thoroughly with a damp cloth. Examples of these materials are: Ceramic cooktop cleaners, tub and tile cleaners, chlorine bleach, oven cleaners, and harsh detergents.

For information regarding touch up and repairs please contact your local representative or call 02 9457 9622.

TECHNICAL ADVANTAGES

Navurban offers consistency in woodgrain structure and tone across each panel, creating the ideal surface for large or small installations. The surface finish offers scratch and abrasion resistance, as well as UV, stain and water resistant; offering savings in fabrication costs and ease of installation. Navurban is available as a finished panel on your substrate if choice, with matching ABS edging to complete the project.

FEATURES & BENEFITS

The hard-wearing decorative surface is a Non PVC decorative sheet with advanced embossing and texture capabilities.

The benefits of Navurban include:

- Extensive range of designs
- Pre finished board
- Colour and grain consistency over a large number of sheets
- Matching ABS edging
- Scratch and abrasion resistance
- High levels UV resistance
- When recycled breaks down to Carbon Dioxide and Water
- Adhered to the substrate using low VOC (Volatile Organic Compound) crosslinking water-based EVA glue

Please refer to the website for full details of Navurban's environmental credentials.

Navurban is produced in Australia to ensure the highest levels of quality and service, no matter how small or large your project.

EDGING

Navurban's matching ABS edging range is available in 1.0mm. The edging is also available in 22mm, 38mm, 45mm and 54mm widths to suit a wide range of panel thicknesses. ABS is a durable edging alternative that is ideal for high traffic areas and suitable for wet areas.

TECHNICAL SPECIFICATIONS

Panel Size

2400mm x 1200mm, 3000mm x 1200mm, 3600mm x 1200mm

Some designs are only available in a 900mm width. Please refer to the Product Specification List for details.

Stock is held in a select range of colours;

2400mm x 1200mm x 19mm and 3600mm x 1200mm x 19mm, 25mm and 33mm. All boards are finished G2S on a E0 MR MDF as a standard.

Made to Order boards will have a 10 work day lead time.

Please note: A 20% surcharge may apply for minimum orders.

For more information on stocked items please contact your local representative or call 02 9457 9622.

GUARANTEE

New Age Veneers Pty Ltd guarantees the intrinsic qualities of Navurban. Discoloration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of New Age Veneers Pty Ltd is limited to the replacement of any material shown to be defective.

New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.